



Pull-wire switch Extreme ZS 71 WZ -40°C IP67 Extreme


Features/Options:

- Cold-resistant down to -40 °C
- High degree of protection IP 67
- Metal enclosure
- On-wall mounting
- Slow action: 2 contacts
- Pull-wire function with latching
- Attention: Please state required international approvals with your order!

Notes

- 1 cable gland M20x1.5 brass nickel-plated included in delivery

Technical data

Applied standards	EN 60947-5-1
Enclosure	aluminium die-cast, powder-coated
Cover	thermoplastic, glass-fibre reinforced, impact resistant, self-extinguishing UL 94 V-0
Degree of protection	IP 67 to IEC/EN 60529
Contact material	silver
Switching system	slow action
Switching elements	1 NC/1 NO contact, type Zb
Connection	screw connection terminals
Cable cross-section	max. 1.5 mm ² (incl. conductor ferrules)
Cable entry	2 x M20 x 1.5
Rated impulse withstand voltage U_{imp}	4 kV
Rated insulation voltage U_i	400 V
Conventional thermal current I_{the}	4 A
Utilisation category	AC-15
Rated operating current/voltage I_g/U_g	4 A/400 VAC
Short-circuit protection	4 A gG/gN fuse
Ambient temperature	-40 °C ... +80 °C
Mechanical life	> 1 million operations
Operation cycles	max. 3600/h
Actuating force	max. 50 N
Approvals	

Errors and omissions excepted.