



Safety sensor Extreme BZ 16 IP69 Extreme

Features/Options:

- Version with higher degree of protection IP69: suitable for cleaning with 80 °C hot water at 100 bar pressure at a distance of 100 mm from different directions
- Thermoplastic enclosure
- Long life
- Differential inputs: Induction / magnetic operating principle
- Internal monitoring, high manipulation protection
- Potential-free outputs
- Signalling contact
- Status LED
- 1 NO/2 NC contact or 3 NC contacts
- Available with 2 different actuating planes:
actuating from the top "T",
actuating from the front "F".
Please indicate the desired actuating plane when ordering.
- Rated switching distance $s_n = 12$ mm
- Wiring compartment
- Attention: Please state required international approvals with your order!

Notes

- 1 cable gland M20x1.5 - IP69 and 2 locking screws M20x1.5 included in delivery
- The actuator is not included in the delivery of the switches

Technical data

Applied standards	EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 61000-6-4, EN 60947-5-2, EN 60947-5-3, EN ISO 14119, EN 60204-1, EN ISO 13849-1, EN 62061, 2004/108/EG
Enclosure	thermoplastic, glass-fibre reinforced, impact resistant, self-extinguishing UL 94 V-0
Defined object	actuator BZ 16-B1 with low coding
Sensor type	type 4 interlocking device
Coding level	low coding
Tightening torque	enclosure mounting screws: max. 2 Nm cover screws: max. 1.5 Nm actuator screws: max. 2 Nm
Degree of protection	IP 69 (IEC/EN 60529)
Safety-relevant data:	
EN ISO 13849-1	Performance Level PL e
Category	3
B_{10d} (10 % load)	20 million
T_M	max. 20 years
$MTTF_d$	100 years
DC/DC _{avg}	96 %
EN 62061	SIL CL 3
PFH_d	$\geq 4.29 \times 10^{-8}$ 1/h

Errors and omissions excepted.



Safety sensor Extreme BZ 16 IP69 Extreme

Technical data	
h_{op}	8 h/day
d_{op}	220 days/year
t_{zyklus}	20 s
Switching distances	$s_n = 12$ mm (10 mm with flush mounting) $s_{ao} = 10$ mm (8 mm with flush mounting) $s_{ar} = 25$ mm (Minimum distance 2 mm for approach from side.)
Hysteresis	approx. 6 mm
Sideways tolerance	≤ 3 mm
Repeatability	± 1 mm
Rated operating current/voltage I_e/U_e	140 mA/24 VDC ± 15 % (reverse voltage protected); output contacts: max. 3 A/24 VAC/DC, min. 10 mA/5 VAC/DC; signalling contact: max. 1 A/24 VAC/DC, min. 100 μ A/100 mVDC
No-load supply current I_0	≤ 70 mA
Short-circuit protection	U_e : 0.25 A (slow blow); output contacts: 4 A (gG/gN) incoming series-connected
Outputs	2 enabling paths (2 NC or 1 NO/1 NC) 1 signalling contact (1 NC)
Switching voltage	max. 30 VAC/DC
Conditional short-circuit current	100 A
Utilisation category	AC-15; DC-13 (output contacts) AC-12; DC-12 (signalling contact)
Rated operating isolation voltage U_i	250 VAC
Rated impulse withstand voltage U_{imp}	1.5 kV
Voltage drop at I_e	max. 0.6 V
Overvoltage category	III
Switching frequency	max. 1 Hz
Attendance delay t_v	< 300 ms
Risk time	max. 165 ms
Degree of pollution	3
Ambient temperature	0 °C ... +55 °C
Storage and shipping temperature	-20 °C ... +70 °C
Mechanical life	50 mio. operations
Contact material	output contacts: AgSnO self-cleaning, positive-guided; signalling contact: AgNi, gold-plated

Errors and omissions excepted.



Safety sensor Extreme BZ 16 IP69 Extreme

Technical data

Contact resistance	output contacts: 100 mΩ in new condition; signalling contact: max. 30 mΩ
Connection	wiring compartment with socket screw clamps 8-pole
Cable entry	3 x M20 x 1.5
Cable cross-section	min. 0.14 mm ² / AWG 28 max. 1.5 mm ² / AWG 16

Approvals



Note The safety-related data are based on a load of 24 V / 0.1 A / DC-1 for the enabling paths. With higher load currents for the enabling paths and other requirement rates n_{op} , the safety-related data vary from the given data and can be provided on request.

Ordering details



3 NC contacts

Type
BZ 16-03F IP69 Extreme
BZ 16-03T IP69 Extreme

Material no.
1355632
1355634



1 NO/2 NC contacts

Type
BZ 16-12F IP69 Extreme
BZ 16-12T IP69 Extreme

Material no.
1355627
1355630

Actuators



Actuating magnet BZ 16-B1
4798

Type
Actuating magnet coded BZ 16-B1

Material no.
1165032

Errors and omissions excepted.



Safety sensor Extreme BZ 16 IP69 Extreme

Accessories



SRM 21 RT2

Type
Safety relay module SRM 21 RT2

Material no.
1179203



SRM 21 Multi

Type
Safety relay module SRM 21 Multi

Material no.
1185607