



## Wireless receivers with gateway RF RxT EN868-USB

### Features/Options:

- Thermoplastic enclosure
- EnOcean® wireless technology
- USB 2.0 transmitter and receiver unit
- Multi-network capable
- Power supply via USB interface
- Support of up to 128 actors and an indefinite number of transmitters

### Technical data

Standards	EN 301 489-1; EN 301 489-3; EN 300 220-2; EN 300 220-3
Number of channels	max. 128 actors, indefinite number of transmitters
Connection	USB 2.0, cable length 0.6 m (without plug-in connector)
Degree of protection	IP 30 to IEC/EN 60529
Inputs	indefinite number of EnOcean® transmitters
Outputs	max. 128 actors
Voltage supply	via USB interface
Frequency	868.3 MHz (EU, Switzerland)
Operation cycles	approx. 9000 telegrams with repetitions/h
Degree of pollution	2 to EN 60664-1 (VDE 0110-1)
Ambient temperature	0 °C ... +55 °C
EMC rating	according to EMC Directive
Dimensions	25 x 125 x 65 mm (H x W x D)
Note	no external antenna required
Weight	80 g

### Ordering details



RF RxT EN868-USB 9114

Type  
RF RxT EN868-USB

Material no.  
1187937

Errors and omissions excepted.